

Triplewide Model (114 ft³)

Interior finish:

22 gauge stainless steel

Exterior finish:

Sprayed enamel over steel



STANDARD OPTIONS:

- Additional Access Ports
- Chart Recorders
- Condensate Removal Options
- Dry Air Tower
- Desiccant Drier
- Interior Receptacle
- International Construction 50 hz/CE
- Electrofin Coil Coating
- Glass Doors
- Interior Lighting
- Mechanical Covers
- Water Cooled Condensing Units
- Mechanical Redundancy

OTHER CHAMBER OFFERINGS:

- CO2 Control
- Clean Room Flush Mount Chambers
- Pass-Thru Chambers
- Programmable Ramping / Freeze Thaw
- Remote Condensing Units



Bahnsen

Environmental Specialties
An EMCOR Company

www.eschambers.com

4412 Tryon Road
Raleigh, NC 27606

t 919.829.9300
f 919.833.9476

Infinitely
Precise.
Ultimately
Reliable.

Model	Interior volume	Temp range	Humidity range	Volumetric uniformity	4-wire electrical volts/Ø/Amps	Int. dimensions WxDxH	Ext. dimensions WxDxH	Shelves Std/max	Weight LBS/KG
-------	-----------------	------------	----------------	-----------------------	--------------------------------	-----------------------	-----------------------	-----------------	---------------

TEMP ONLY:

A-TW	114.8 ft ³ (3251 liters)	35 to 70 °C	N/A	±1.0 °C	208-230 / 1 / 30	116 x 28.5 x 60 in. (295 x 73 x 153 cm)	123 x 34.5 x 91.5 in. (312 x 88 x 233 cm)	12/57	1420/644
C-TW		2 to 70 °C	N/A						1520/689

TEMP AND HUMIDITY:

AM-TW	114.8 ft ³ (3251 liters)	35 to 70 °C	10-96%	±1.0 °C ±5.0% RH	208-230 / 1 / 30	116 x 28.5 x 60 in. (295 x 73 x 153 cm)	123 x 34.5 x 91.5 in. (312 x 88 x 233 cm)	12/57	1460/662
CDM-TW		2 to 70 °C	10-96%						1570/712

LOW TEMPERATURE:

C-TW-LT	114.8 ft ³ (3251 liters)	-30 to 70 °C	N/A	±1.0 °C	208-230 / 1 / 30	116 x 28.5 x 60 in. (295 x 73 x 153 cm)	123 x 34.5 x 91.5 in. (312 x 88 x 233 cm)	12/57	1570/712
CDM-TW-LT			10-96%	±1.0 °C ±5.0% RH					1620/735

LOW HUMIDITY:

CDMD-TW	114.8 ft ³ (3251 liters)	2 to 70 °C	10-96%	±1.0 °C ±5.0% RH	208-230 / 1 / 30	116 x 28.5 x 60 in. (295 x 73 x 153 cm)	123 x 34.5 x 91.5 in. (312 x 88 x 233 cm)	12/57	1600/726
CDM-TW-AT			10-96%						1640/744