

Doublewide Model (74 ft³)

Interior finish:

22 gauge stainless steel

Exterior finish:

Sprayed enamel over steel

STANDARD OPTIONS:

- Additional Access Ports
- Chart Recorders
- Condensate Removal Options
- Dry Air Tower
- Desiccant Drier
- Interior Receptacle
- International Construction 50 hz/CE
- Electrofin Coil Coating
- Glass Doors
- Interior Lighting
- Mechanical Covers
- Water Cooled Condensing Units
- Mechanical Redundancy



OTHER CHAMBER OFFERINGS:

- CO2 Control
- Clean Room Flush Mount Chambers
- Pass-Thru Chambers
- Programmable Ramping / Freeze Thaw
- Remote Condensing Units



Bahnsen

Environmental Specialties

An EMCOR Company

www.eschambers.com

4412 Tryon Road
Raleigh, NC 27606

t 919.829.9300

f 919.833.9476

**Infinitely
Precise.
Ultimately
Reliable.**

Model	Interior volume	Temp range	Humidity range	Volumetric uniformity	4-wire electrical volts/Ø/Amps	Int. dimensions WxDxH	Ext. dimensions WxDxH	Shelves Std/max	Weight LBS/KG
-------	-----------------	------------	----------------	-----------------------	--------------------------------	-----------------------	-----------------------	-----------------	---------------

TEMP ONLY:

A-DW	74.2 ft ³ (2101 liters)	35 to 70 °C	N/A	±1.0 °C	208-230 / 1 / 30	75 x 28.5 x 60 in. (191 x 73 x 153 cm)	82 x 34.5 x 91.5 in. (208 x 88 x 233 cm)	8/38	1020/463
C-DW		2 to 70 °C	N/A						1120/508

TEMP AND HUMIDITY:

AM-DW	74.2 ft ³ (2101 liters)	35 to 70 °C	10-96%	±1.0 °C ±5.0% RH	208-230 / 1 / 30	75 x 28.5 x 60 in. (191 x 73 x 153 cm)	82 x 34.5 x 91.5 in. (208 x 88 x 233 cm)	8/38	1060/481
CDM-DW		2 to 70 °C	10-96%						1170/531

LOW TEMPERATURE:

C-DW-LT	74.2 ft ³ (2101 liters)	-30 to 70 °C	N/A	±1.0 °C	208-230 / 1 / 30	75 x 28.5 x 60 in. (191 x 73 x 153 cm)	82 x 34.5 x 91.5 in. (208 x 88 x 233 cm)	8/38	1170/531
CDM-DW-LT			10-96%	±1.0 °C ±5.0% RH					1220/553

LOW HUMIDITY:

CDMD-DW	74.2 ft ³ (2101 liters)	2 to 70 °C	10-96%	±1.0 °C ±5.0% RH	208-230 / 1 / 30	75 x 28.5 x 60 in. (191 x 73 x 153 cm)	82 x 34.5 x 91.5 in. (208 x 88 x 233 cm)	8/38	1200/544
CDM-DW-AT		2 to 70 °C	10-96%						1240/562