

Compact Model (25 ft³)

Interior finish:

22 gauge stainless steel

Exterior finish:

Sprayed enamel over steel

STANDARD OPTIONS:

- Additional Access Ports
- Chart Recorders
- Condensate Removal Options
- Dry Air Tower
- Desiccant Drier
- Interior Receptacle
- International Construction 50 hz/CE
- Electrofin Coil Coating
- Glass Doors
- Interior Lighting
- Mechanical Covers
- Water Cooled Condensing Units



OTHER CHAMBER OFFERINGS:

- CO₂ Control
- Clean Room Flush Mount Chambers
- Pass-Thru Chambers
- Programmable Ramping / Freeze Thaw
- Remote Condensing Units



Bahnsen

Environmental Specialties

An EMCOR Company

www.eschambers.com

4412 Tryon Road
Raleigh, NC 27606

t 919.829.9300

f 919.833.9476

**Infinitely
Precise.
Ultimately
Reliable.**

Model	Interior volume	Temp range	Humidity range	Volumetric uniformity	4-wire electrical volts/Ø/Amps	Int. dimensions WxDxH	Ext. dimensions WxDxH	Shelves Std/max	Weight LBS/KG
-------	-----------------	------------	----------------	-----------------------	--------------------------------	-----------------------	-----------------------	-----------------	---------------

TEMP ONLY:

A-C	25.2 ft ³ (714 liters)	35 to 70 °C	N/A	±0.3 °C	208-230 / 1 / 30	34 x 28.5 x 45 in. (87 x 73 x 114 cm)	41 x 34.5 x 76.5 in. (104 x 88 x 194 cm)	4/14	425/193
C-C		2 to 70 °C	N/A						675/306

TEMP AND HUMIDITY:

AM-C	25.2 ft ³ (714 liters)	35 to 70 °C	10-96%	±0.3 °C ±3.0% RH	208-230 / 1 / 30	34 x 28.5 x 45 in. (87 x 73 x 114 cm)	41 x 34.5 x 76.5 in. (104 x 88 x 194 cm)	4/14	500/227
CDM-C		2 to 70 °C	10-96%						720/327

LOW TEMPERATURE:

C-C-LT	25.2 ft ³ (714 liters)	-30 to 70 °C	N/A	±0.3 °C	208-230 / 1 / 30	34 x 28.5 x 45 in. (87 x 73 x 114 cm)	41 x 34.5 x 76.5 in. (104 x 88 x 194 cm)	4/14	720/327
CDM-C-LT			10-96%	±0.3 °C ±3.0% RH					765/347

LOW HUMIDITY:

CDMD-C	25.2 ft ³ (714 liters)	2 to 70 °C	10-96%	±0.3 °C ±3.0% RH	208-230 / 1 / 30	34 x 28.5 x 45 in. (87 x 73 x 114 cm)	41 x 34.5 x 76.5 in. (104 x 88 x 194 cm)	4/14	750/340
CDM-C-AT		2 to 70 °C	10-96%						750/340